

RANGER 500



ENGINE & DRIVETRAIN

Displacement / Engine Type 500cc / 4-Stroke SOHC Single Cylinder

Drive System True On-Demand AWD/2WD/VersaTrac Turf Mode

Horsepower / Torque 32 hp @ 6350 RPM / 39 Nm @ 5200 RPM

SUSPENSION

Front Suspension MacPherson Strut with 22.9 cm Travel

Rear Suspension Dual A-Arm, IRS with 25.4 cm Travel

Front / Rear Tyres 25 x 8-12; 489 / 25 x 10-12; 489

Wheels Stamped Steel

DIMENSIONS

Dump Box Capacity 226.8 kg

Towing Capacity 680 kg

Fuel Capacity 34.1 L

Ground Clearance 25.4 cm

Vehicle Size (L x W x H) 279 x 147 x 185 cm

Payload Capacity 454 kg

Passenger Capacity 2

Wheelbase 185.4 cm

Dry Weight 490 kg

ADDED FEATURES

Seat Belt Interlock Governs speed to 24 km/h when the driver's Seat Belt is not engaged.


Speed Key Ready This model can readily accept the Speed Key Accessory. Speed Key governs speed to 40 km/h



44 HP




ON DEMAND TRUE ALL-WHEEL-DRIVE (AWD)



UNLOCKING REAR DIFF



IRS WITH 25.4CM OF TRAVEL



DUMP BOX CAPACITY - 227KG



SEAT BELT INTERLOCK



SPEED KEY READY